DIGIVIEW PC04/PC06/PC07 MANUAL (ENG) SIZE: W65 X H105 (mm) BY WING TSUI 22/1007 TABLE OF CONTENTS INTRODUCTION INTRODUCTION 3 ABOUT HIDEKI ELECTRONICS ABOUT HIDEKI ELECTRONICS 3 ABOUT HIDEKI ELECTRONICS TIME PROJECTION 3 CORRENT TIME PROJECTION BATTERY INSTALLATION 7 TIME PROJECTION TIME PROJECTION 8 CURRENT TIME PROJECTION CALENDAR AND CLOCK DISPLAY MODES 9 Visit our website (www. digite/writine.com) to learn more yest the duit be file illectronics stock as precise	
INTRODUCTION 3 ABOUT HIDEKI ELECTRONICS 3 ABOUT HIDEKI ELECTRONICS 3 ABOUT OVERVIEW 4 GETTING STARTED 7 BATTERY INSTALLATION 7 TIME PROJECTION 8 CURRENT TIME PROJECTION 9 ABOUT HIDEKI ELECTRONICS 9	
SETTING THE CLOCK 10 advoices, environmental products and projection time pieces, environmental products and	ramming isplay les and allows setting Action rm/chime on/off n Hour n Minutes th Hour Minutes th NT

TIME PROJECTION

The Sport Alarm Clock can project the time display for a short period when operating on batteries, or continuously when using the AC/DC adapter. The clock is designed to

<figure><figure><image/></figure></figure>	CONTINUOUS TIME PROJECTION Connect AC/DC adapter (optional) to project the time display continuously. CALENDAR AND CLOCK DISPLAY MODES The Alarm Clock has a three (3) display modes: TIME, DATE and ALARM The current time is displayed in hour-minutes format which is the default display mode. The date is displayed in month-date format. The alarm time is displayed in hour-minutes format. The alarm time is displayed in hour-minutes format.
 SETTING THE CLOCK <i>TIME AND DATE</i> After batteries are installed as shown inside the battery compartment, the default time will be displayed as "1:00" To set current date and time: Press SET button 4 times, and the MONTH will be displayed as "1". Press MODE button to set the current month. Press SET button and the DAY will be displayed. Press MODE button to set the current day. Press MODE button to set the current day. Press SET button again and the HOUR will be displayed as 1: A. Press SET button nad the MINUTES will be displayed. Press SET button nad the MINUTES will be displayed. Press SET button to set current hour (AM, 24 hour, PM). Press SET button to set the correct minute. Press MODE button to set the correct minute. Press MODE button to return clock to normal operation. 24 HOUR TIME FORMAT Press MODE button to "12 hour" format continue pressing MODE. 	ALARM If the alarm is activated, it will sound at the set time and the (bell icon) will flash. To review the alarm time, press MODE button once in TIME display and the default alarm time will be displayed as "1:00" and "ALARM" will be displayed in the top left of the LCD display. To review the date, press MODE button when the ALARM TIME is displayed. When MODE is pressed again the seconds will be displayed. To return to the TIME display, press MODE button again or wait for it to change back. TO SET ALARM TIME Press SET button twice in TIME display. If the alarm is being set for the first time, "1:4" will be displayed with flashing, and "ALARM" will display in the top left. Press MODE button to adjust the desired alarm HOUR. Press SET button to adjust the desired alarm HOUR. Press SET button to adjust the desired alarm minutes. "O" will flash. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desired alarm minutes. Press SET button to adjust the desined alarm min

CURRENT TIME PROJECTION

the ceiling for 3 seconds.

Press "LIGHT/SNOOZE" button to turn on the LCD backlight and project the time display onto the wall or

ENABLE OR DISABLE ALARM AND CHIME • Press SET button in TIME display mode. Alarm hour and minute digits will flash. • Press MODE button to enable or disable the alarm and chime in the following sequence: 1:00

ALARM ON- ALARM&CHIMEON-	

CHIME ON-ALARM&CHIME OFF -ALARM ON-

1:00 • Press SET button to confirm the alarm and chime status. Clock will go into TIME and DATE set mode. Wait and clock will return to TIME display mode.

1:00

1:00

TO STOP ALARM

To stop the alarm for 24 hours, press SET when alarm is activated. To stop alarm for 5 minutes, press SNOOZE/LIGHT

button If no button is pressed, alarm will stop in 2 minutes. Press **MODE** button to disable the alarm in **ALARM** display format while alarm time digits are flashing. (The bell icon will disappear from the display when

alarm is disabled).

CHIME When CHIME is activated, it will sound at every hour.

12

PRECAUTIONS

This product is engineered to give you years of satisfactory service if handled carefully. Here are a few precautions:

1. Do not immerse the unit in water.

- 2. Do not clean the unit with abrasive or corrosive materials. They may scratch the plastic parts and corrode the electronic circuits.
- Do not subject the product to excessive force, shock, dust, temperature, or humidity, which may result in malfunctions, shorter lifespan, damaged batteries, and damaged parts.
- Do not tamper with the unit's internal components. Doing so will invalidate the warranty and may cause damage. This unit contains no user-serviceable parts. 5. Use only fresh batteries. Do not mix new and old
- batteries. 6. Read the user's manual thoroughly before operating

the unit.

SPECIFICATIONS

Projection Current time display projected onto the ceiling or wall Fixed red display projection

Calendar and Clock

12/24 hour display in hh : mm format Date Format: Month - Day format Single 2-minute crescendo alarm with snooze and chime LED backlight

Power

2 AAA batteries (not included) AC/DC Adapter (3V, 100mA), center pin positive (optional)

Dimensions 4.33 (L) x 4.72 (H) x 4.33 (D) inches 13

I		
SETTING THE CLOCK TIME AND DATE After batteries are installed as shown inside the battery compartment, the default time will be displayed as "1:00" To set current date and time: 1). Press SET button 4 times, and the MONTH will be displayed as "1". 2). Press MODE button to set the current month. 3). Press SET button and the DAY will be displayed. 4). Press MODE button to set the current day. 5). Press SET button again and the HOUR will be displayed as 1: A. 6). Press SET button to set current hour (AM, 24 hour, PM). 7). Press SET button to set the correct minute. 8). Press MODE button to set the correct minute. 9). Press MODE button to return clock to normal operation. 24 HOUR TIME FORMAT Press MODE button until the desired hour in "24 hour" format is shown. To return to "12 hour" format continue pressing MODE.	 ALARM If the alarm is activated, it will sound at the set time and the (bell icon) will flash. To review the alarm time, press MODE button once in TIME display and the default alarm time will be displayed as "1:00" and "ALARM" will be displayed in the top left of the LCD display. To review the date, press MODE button when the ALARM TIME is displayed. When MODE is pressed again the seconds will be displayed. To return to the TIME display, press MODE button again or wait for it to change back. TO SET ALARM TIME for the first time, "1:A" will be displayed with flashing, and "ALARM" will display in the top left. Press MODE button to adjust the desired alarm MINUTES, the alarm minutes "00" will flash. Press SET button to adjust the desired alarm MINUTES, the alarm minutes "00" will flash. Press SET button to adjust the desired alarm minutes. Press SET button to the TIME display mode. 	 STANDARD WARRANTY INFORMATION This product is warranted from the manufacturing defects for one year from date of retail purchase. It does not cover damages or wear resulting from accident, misuse, abuse, commercial use, or unauthorized adjustment and/ or repair. Note that online product registration is required to ensure valid warranty protection. To register your product, go to our Company website at: www.digivewtime.us. Click Online Product Registration under the Customer Service menu. Should you require assistance with this product and its operation, please contact our Customer Service Hotline 1(866) 443 3543 Please direct all returns to the place of the original purchase. Should this not be possible, contact Customer Service Hotline for assistance and to obtain a Return Merchandise Authorization (RMA). Returns without a return authorization will be refused. Please retain your original receipt as you may be asked to provide a copy for proof of purchase. Hideki Electronics, Inc. reserves the right to repair or replace the product at our option.

10

14

15